



Minimum Evaporating Temp. With:

10 K Suction Superheat

Maximum Evaporating Temperature

Suction Superheat 5.0K

Liquid Subcooling 4.0K

Evaporating Temperature, °C

Cond °C	Cooling Capacity, kW											
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5	15.0	20.0	25.0
10.0	21.10	26.50	33.00									
15.0	19.90	25.10	31.40	38.90								
20.0	18.65	23.60	29.70	36.90	45.50							
25.0	17.35	22.20	28.00	35.00	43.20	52.80	57.10					
30.0	16.10	20.70	26.30	32.90	40.80	50.00	54.10	60.70	66.60			
35.0	14.80	19.20	24.50	30.90	38.40	47.20	51.10	57.40	63.10	69.20		
40.0	13.50	17.70	22.80	28.80	36.00	44.40	48.10	54.10	59.50	65.40	78.30	92.90
45.0	12.15	16.20	21.00	26.80	33.50	41.50	45.00	50.80	55.90	61.50	73.80	87.80
50.0	10.85	14.70	19.25	24.70	31.10	38.60	41.90	47.40	52.30	57.60	69.30	82.70
55.0	9.57	13.20	17.45	22.60	28.60	35.70	38.80	44.00	48.60	53.60	64.80	77.50
60.0		11.70	15.70	20.40	26.10	32.80	35.70	40.60	44.90	49.70	60.20	72.30
65.0			13.90	18.35	23.60	29.80	32.60	37.10	41.30	45.70	55.60	67.10
70.0			12.15	16.25	21.10	26.90	29.50	33.70	37.60	41.70	51.00	61.80
75.0				14.15	18.60	23.90	26.40	30.30	33.90	37.70	46.50	
80.0				12.05	16.15	21.00	23.20	26.90	30.20	33.80	41.90	

Cond °C	Power, kW											
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5	15.0	20.0	25.0
10.0	5.12	5.30	5.31									
15.0	5.55	5.84	5.99	5.96								
20.0	5.95	6.36	6.64	6.75	6.67							
25.0	6.31	6.83	7.25	7.51	7.60	7.46	7.34					
30.0	6.63	7.27	7.82	8.23	8.48	8.53	8.49	8.35	8.15			
35.0	6.91	7.66	8.34	8.90	9.32	9.55	9.59	9.57	9.48	9.33		
40.0	7.13	8.00	8.81	9.52	10.10	10.50	10.65	10.75	10.75	10.70	10.40	9.81
45.0	7.29	8.28	9.22	10.10	10.85	11.45	11.65	11.85	12.00	12.05	12.00	11.60
50.0	7.39	8.50	9.57	10.60	11.50	12.30	12.55	12.90	13.15	13.30	13.50	13.35
55.0	7.42	8.64	9.85	11.00	12.10	13.05	13.40	13.90	14.20	14.50	14.90	15.05
60.0		8.71	10.05	11.35	12.60	13.75	14.20	14.80	15.25	15.65	16.25	16.65
65.0			10.20	11.65	13.05	14.40	14.90	15.60	16.15	16.70	17.55	18.20
70.0			10.20	11.85	13.40	14.95	15.50	16.35	17.00	17.65	18.75	19.65
75.0				11.90	13.70	15.40	16.05	17.00	17.75	18.50	19.85	
80.0				11.90	13.85	15.75	16.45	17.55	18.45	19.25	20.80	

Cond °C	Current at 400 V, A											
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5	15.0	20.0	25.0
10.0	17.27	17.42	17.41									
15.0	17.65	17.92	18.06	18.00								
20.0	18.02	18.42	18.71	18.83	18.71							
25.0	18.38	18.91	19.35	19.65	19.73	19.56	19.40					
30.0	18.71	19.37	19.97	20.44	20.74	20.79	20.73	20.54	20.29			
35.0	19.01	19.80	20.56	21.21	21.71	22.00	22.04	22.01	21.89	21.69		
40.0	19.25	20.18	21.10	21.94	22.65	23.17	23.31	23.44	23.46	23.40	23.00	22.17
45.0	19.43	20.51	21.59	22.62	23.54	24.30	24.54	24.83	24.99	25.08	24.98	24.49
50.0	19.54	20.76	22.01	23.23	24.37	25.37	25.71	26.16	26.47	26.70	26.92	26.76
55.0	19.56	20.93	22.34	23.76	25.12	26.36	26.81	27.43	27.88	28.26	28.79	28.98
60.0		21.00	22.59	24.21	25.79	27.28	27.83	28.61	29.21	29.74	30.60	31.12
65.0			22.74	24.56	26.36	28.10	28.76	29.71	30.45	31.13	32.31	33.19
70.0			22.77	24.79	26.83	28.82	29.59	30.70	31.59	32.43	33.93	35.16
75.0				24.90	27.17	29.41	30.29	31.58	32.62	33.61	35.44	
80.0				24.88	27.38	29.88	30.87	32.33	33.52	34.67	36.84	

Cond °C	Suction Mass Flow, g/s											
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5	15.0	20.0	25.0
10.0	116.00	143.00	175.00									
15.0	113.50	140.50	172.50	210.00								
20.0	111.00	138.00	170.00	208.00	252.00							
25.0	108.00	135.00	167.00	205.00	248.00	298.00	320.00					
30.0	104.50	132.00	164.00	201.00	245.00	295.00	317.00	352.00	383.00			
35.0	101.00	128.00	160.50	198.00	241.00	291.00	312.00	347.00	378.00	411.00		
40.0	96.80	124.50	156.50	194.00	237.00	286.00	308.00	342.00	373.00	406.00	478.00	558.00
45.0	92.40	120.00	152.00	189.50	232.00	281.00	303.00	337.00	368.00	401.00	472.00	552.00
50.0	87.50	115.50	147.50	184.50	227.00	276.00	297.00	332.00	362.00	395.00	466.00	546.00
55.0	82.20	110.50	142.50	179.00	221.00	270.00	291.00	326.00	356.00	388.00	459.00	539.00
60.0		104.50	136.50	173.50	215.00	264.00	285.00	319.00	349.00	382.00	452.00	532.00
65.0			130.50	167.00	209.00	257.00	278.00	312.00	342.00	374.00	445.00	525.00
70.0			123.50	160.00	202.00	249.00	271.00	304.00	335.00	367.00	438.00	518.00
75.0				152.00	194.00	242.00	263.00	296.00	327.00	359.00	430.00	
80.0				143.50	185.50	233.00	255.00	289.00	319.00	352.00	423.00	

**COMPRESSOR MECHANICAL AND PHYSICAL DATA**

Number of cylinders	4
Displacement @ 50 Hz, m <sup>3</sup> /h	70.8
Bore/Stroke, mm	68.3/55.6
Length/Width, mm	670/490
Height, mm	495
Net Weight, kg	194
Gross Weight, kg	210
Suction, inch	2 1/8
Discharge, inch	1 1/8
Drive Frequency Range, Hz	25 - 60
Oil Quantity, l	3.3
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF, POE MOBIL EAL Arctic 22 CC
Base mounting (hole dia), mm	381 x 305 (18)
Sound Pressure @ 1m (MT), dBA	71
Sound Power (MT), dBA	82
Sound Conditions (MT, Temperatures: Evap./Cond./Suction at freq./speed)	-10 / 45 / 20 °C at 50 Hz
Sound Pressure @ 1m (HT), dBA	71
Sound Power (HT), dBA	82
Sound Conditions (HT, Temperatures: Evap./Cond./Suction at freq./speed)	5 / 50 / 15 °C at 50 Hz
High Side PS gauge, bar	32.5
Low Side PS gauge, bar	22.5
Refrigerant's GWP	1430
Refrigerant's classification	A1

**COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)**

Maximum Operating Current, A	41
Locked Rotor Current, A	199
Default Enclosure Class	IP 54 (IEC 34)

**ACCESSORIES INCLUDED**

Oil Pressure Switch	OPS2 Sensor
Mounting Springs	4

### ACCESSORIES OPTIONAL

Additional Cooling	70 W Vertical Air Flow Fan
Capacity Control	Capacity Steps 50%
Crankcase Heater	100 W Internal
Discharge Temperature Protection	Head PTC sensor
Enclosure Class	IP 56
Oil Pressure Switch	OPS2 Electronic Switch
Unloaded start	Available
Deep Oil Sump	Mounted
Adapter Kit	For Parallel Operation
Check Valve	For unloaded start operation
Oil Control System	ALCO Trax-Oil OM3

### MOTOR OPTIONS

<i>Motor Code</i>	<i>Power Supply</i>	<i>Nominal Voltage, V</i>	<i>Start Connection</i>	<i>DOL Connection</i>	<i>Amps Factor</i>
AWM	380-420 V / 3~ / 50 Hz	400	YY/Y	Y	1.00
EWL	220-240 V / 3~ / 50 Hz	230	Y/DELTA	DELTA	1.73
EWL	380-420 V / 3~ / 50 Hz	400		Y	1.00
EWM	380-420 V / 3~ / 50 Hz	400	Y/DELTA	DELTA	1.00
EWY	500-550 V / 3~ / 50 Hz	525	Y/DELTA	DELTA	0.76
AWR	220-240 V / 3~ / 50 Hz	230	YY/Y	Y	1.73
AWY	500-550 V / 3~ / 50 Hz	525	YY/Y	Y	0.76
TWY	500-550 V / 3~ / 50 Hz	525		DELTA	0.76
EWK	220-240 V / 3~ / 60 Hz	230	Y/DELTA	DELTA	2.10
EWK	380-420 V / 3~ / 60 Hz	380		Y	1.20
EWD	440-480 V / 3~ / 60 Hz	460	Y/DELTA	DELTA	1.00
AWC	208-230 V / 3~ / 60 Hz	230	YY/Y	Y	2.19
AWX	380 V / 3~ / 60 Hz	380	YY/Y	Y	1.20
AWD	440-480 V / 3~ / 60 Hz	460	YY/Y	Y	1.00