



Minimum Evaporating Temp. With:

- 25 °C Suction Gas Return
- Maximum Evaporating Temperature

Suction Superheat 11.1K

Liquid Subcooling 8.3K

Evaporating Temperature, °C

Cond °C	Cooling Capacity, kW								
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5
10.0	46.30	58.90	74.00						
15.0	43.60	55.70	70.30	87.60					
20.0	40.90	52.60	66.60	83.20	103.00				
25.0	38.10	49.40	62.90	78.80	97.50	119.50			
30.0	35.40	46.20	59.10	74.40	92.30	113.00	122.50	137.00	150.50
35.0	32.70	43.00	55.40	69.90	87.00	107.00	116.00	130.00	143.00
40.0	30.00	39.90	51.60	65.50	81.80	101.00	109.50	123.00	135.00
45.0	27.40	36.80	47.90	61.10	76.50	94.70	102.50	115.50	127.50
50.0	24.90	33.80	44.30	56.70	71.30	88.50	96.20	108.50	119.50
55.0	22.50	30.90	40.80	52.40	66.20	82.40	89.70	101.50	112.00
60.0	20.30	28.10	37.30	48.20	61.10	76.40	83.20	94.40	104.50
62.0			36.00	46.50	59.10	74.00	80.70	91.60	101.50

Cond °C	Power, kW								
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5
10.0	11.50	12.20	12.65						
15.0	12.35	13.25	14.00	14.45					
20.0	13.05	14.25	15.25	16.05	16.50				
25.0	13.70	15.10	16.40	17.45	18.30	18.80			
30.0	14.25	15.90	17.45	18.80	19.95	20.80	21.10	21.40	21.50
35.0	14.75	16.60	18.35	20.00	21.50	22.70	23.20	23.70	24.00
40.0	15.15	17.20	19.20	21.10	22.90	24.50	25.10	25.90	26.40
45.0	15.50	17.70	19.95	22.20	24.30	26.20	26.90	27.90	28.70
50.0	15.75	18.15	20.60	23.10	25.50	27.80	28.60	29.90	30.80
55.0	16.00	18.55	21.20	24.00	26.60	29.20	30.20	31.70	32.80
60.0	16.15	18.90	21.80	24.70	27.70	30.60	31.80	33.40	34.80
62.0			22.00	25.00	28.10	31.10	32.30	34.10	35.50

Cond °C	Current at 400 V, A								
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5
10.0	30.40	30.58	30.69						
15.0	31.02	31.59	32.13	32.49					
20.0	31.58	32.52	33.48	34.30	34.85				
25.0	32.10	33.39	34.75	36.01	37.05	37.71			
30.0	32.58	34.20	35.93	37.63	39.14	40.32	40.67	41.02	41.14
35.0	33.00	34.95	37.05	39.15	41.12	42.81	43.37	44.06	44.48
40.0	33.39	35.64	38.08	40.58	43.00	45.17	45.94	46.95	47.66
45.0	33.74	36.27	39.04	41.93	44.76	47.40	48.38	49.71	50.69
50.0	34.05	36.84	39.94	43.18	46.42	49.52	50.69	52.33	53.57
55.0	34.32	37.36	40.76	44.34	47.98	51.52	52.87	54.81	56.31
60.0	34.55	37.84	41.51	45.43	49.44	53.39	54.93	57.15	58.91
62.0			41.79	45.83	49.99	54.11	55.72	58.05	59.91

50 Hz

6SU-400

R134a

Cond °C	Suction Mass Flow, g/s								
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5
10.0	240.00	299.00	370.00						
15.0	234.00	294.00	364.00	447.00					
20.0	228.00	288.00	358.00	440.00	534.00				
25.0	221.00	281.00	351.00	433.00	526.00	632.00			
30.0	214.00	274.00	344.00	425.00	518.00	623.00	669.00	743.00	808.00
35.0	207.00	267.00	336.00	416.00	509.00	614.00	660.00	733.00	798.00
40.0	199.50	259.00	328.00	408.00	499.00	604.00	649.00	722.00	787.00
45.0	191.50	251.00	320.00	399.00	489.00	593.00	638.00	711.00	775.00
50.0	183.50	243.00	311.00	389.00	479.00	582.00	627.00	699.00	763.00
55.0	176.00	235.00	302.00	380.00	469.00	571.00	615.00	687.00	751.00
60.0	168.50	227.00	294.00	370.00	458.00	559.00	603.00	675.00	739.00
62.0			290.00	366.00	454.00	554.00	599.00	670.00	734.00

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Number of cylinders	6
Displacement @ 50 Hz, m ³ /h	152
Bore/Stroke, mm	80.6/57.0
Length/Width, mm	740/540
Height, mm	545
Net Weight, kg	265
Gross Weight, kg	281
Suction, inch	2 5/8
Discharge, inch	1 5/8
Drive Frequency Range, Hz	25 - 60
Oil Quantity, l	6.8
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF, POE MOBIL EAL Arctic 22 CC
Base mounting (hole dia), mm	381 x 305 (18)
High Side PS gauge, bar	32.5
Low Side PS gauge, bar	22.5
Refrigerant's GWP	1430
Refrigerant's classification	A1

COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)

Maximum Operating Current, A	73.7
Locked Rotor Current, A	306
Default Enclosure Class	IP 54 (IEC 34)

ACCESSORIES INCLUDED

Oil Pressure Switch	OPS2 Sensor
Mounting Springs	4
Deep Oil Sump	Mounted

ACCESSORIES OPTIONAL

Additional Cooling	70 W Vertical Air Flow Fan
Capacity Control	Capacity Steps 66/33%
Crankcase Heater	200 W Internal
Discharge Temperature Protection	Head PTC sensor
Enclosure Class	IP 56
Oil Pressure Switch	OPS2 Electronic Switch
Unloaded start	Available
Adapter Kit	For Parallel Operation
Check Valve	For unloaded start operation
Oil Control System	ALCO Trax-Oil OM3

MOTOR OPTIONS

<i>Motor Code</i>	<i>Power Supply</i>	<i>Nominal Voltage, V</i>	<i>Start Connection</i>	<i>DOL Connection</i>	<i>Amps Factor</i>
AWM	380-420 V / 3~ / 50 Hz	400	YYY	Y	1.00
EWL	220-240 V / 3~ / 50 Hz	230	Y/DELTA	DELTA	1.73
EWL	380-420 V / 3~ / 50 Hz	400		Y	1.00
AWR	220-240 V / 3~ / 50 Hz	230	YYY	Y	1.73
EWK	220-240 V / 3~ / 60 Hz	230	Y/DELTA	DELTA	2.10
EWK	380-420 V / 3~ / 60 Hz	380		Y	1.20
AWX	380 V / 3~ / 60 Hz	380	YYY	Y	1.20
AWD	440-480 V / 3~ / 60 Hz	460	YYY	Y	1.00