



Minimum Evaporating Temp. With:

- 25 °C Suction Gas Return
- 10 K Suction Superheat
- Maximum Evaporating Temperature

Suction Superheat 10.0K

Liquid Subcooling 0.0K

Evaporating Temperature, °C

Cond °C	Cooling Capacity, kW									
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5	15.0
30.0	1.62	2.14	2.73	3.41	4.21	5.15	5.57	6.25		
35.0	1.48	1.99	2.56	3.22	3.99	4.89	5.29	5.95	6.54	
40.0	1.34	1.85	2.40	3.04	3.77	4.63	5.02	5.65	6.22	6.83
45.0		1.71	2.25	2.85	3.56	4.38	4.75	5.34	5.89	6.48
50.0		1.56	2.08	2.67	3.34	4.12	4.47	5.04	5.56	6.12
55.0			1.92	2.47	3.11	3.85	4.18	4.72	5.21	5.75
60.0				2.27	2.88	3.58	3.89	4.40	4.86	5.36
65.0				2.06	2.63	3.28	3.58	4.06	4.49	4.97
70.0					2.36	2.98	3.25	3.70	4.10	4.55
75.0					2.08	2.65	2.90	3.31	3.69	4.11

50 Hz		ZR28K3E-PFJ								R134a	
Cond °C	Power, kW										
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5	15.0	
30.0	0.91	0.90	0.90	0.90	0.90	0.90	0.90	0.89			
35.0	1.01	1.01	1.02	1.02	1.02	1.02	1.02	1.02	1.01		
40.0	1.12	1.12	1.12	1.12	1.13	1.13	1.13	1.13	1.13	1.12	
45.0		1.24	1.24	1.24	1.25	1.25	1.25	1.25	1.25	1.25	
50.0		1.38	1.38	1.38	1.38	1.38	1.38	1.38	1.38	1.38	
55.0			1.54	1.53	1.53	1.53	1.53	1.53	1.52	1.52	
60.0				1.72	1.72	1.71	1.70	1.70	1.70	1.70	
65.0				1.95	1.94	1.93	1.92	1.92	1.92	1.91	
70.0					2.21	2.19	2.19	2.18	2.17	2.16	
75.0					2.54	2.51	2.50	2.49	2.48	2.47	
Cond °C	Current at 230 V, A										
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5	15.0	
30.0	4.96	4.95	4.95	4.96	4.96	4.94	4.92	4.89			
35.0	5.36	5.35	5.36	5.38	5.40	5.40	5.39	5.38	5.35		
40.0	5.78	5.77	5.78	5.81	5.83	5.85	5.85	5.84	5.83	5.80	
45.0		6.24	6.25	6.27	6.30	6.32	6.32	6.32	6.32	6.30	
50.0		6.81	6.81	6.82	6.84	6.86	6.86	6.86	6.86	6.85	
55.0			7.49	7.48	7.49	7.50	7.50	7.50	7.49	7.48	
60.0				8.30	8.29	8.28	8.28	8.27	8.25	8.24	
65.0				9.32	9.28	9.24	9.23	9.21	9.19	9.16	
70.0					10.50	10.43	10.40	10.37	10.33	10.29	
75.0					11.98	11.87	11.83	11.77	11.72	11.67	
Cond °C	Suction Mass Flow, g/s										
	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0	10.0	12.5	15.0	
30.0	10.60	13.75	17.20	21.00	25.50	30.60	32.80	36.40			
35.0	10.20	13.45	16.95	20.80	25.30	30.40	32.60	36.20	39.50		
40.0	9.80	13.15	16.70	20.60	25.10	30.20	32.40	36.00	39.30	42.80	
45.0		12.85	16.45	20.40	24.90	30.00	32.20	35.80	39.10	42.60	
50.0		12.50	16.20	20.20	24.70	29.80	32.00	35.60	38.90	42.30	
55.0			15.90	19.95	24.50	29.60	31.80	35.40	38.60	42.10	
60.0				19.60	24.10	29.20	31.50	35.10	38.30	41.70	
65.0				19.15	23.70	28.80	31.00	34.60	37.80	41.30	
70.0					23.10	28.20	30.40	34.00	37.30	40.70	
75.0					22.20	27.40	29.70	33.30	36.50	40.00	

### **COMPRESSOR MECHANICAL AND PHYSICAL DATA**

Displacement @ 50 Hz, m <sup>3</sup> /h	6.83
Length/Width, mm	246/246
Height, mm	377
Net Weight, kg	25.4
Gross Weight, kg	29
Stub Suction, inch	3/4
Stub Discharge, inch	1/2
Oil Quantity, l	1.12
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF, POE MOBIL EAL Arctic 22 CC
Base mounting (hole dia), mm	190 x 190 (8.5)
Sound Pressure @ 1m (HT), dBA	54
Sound Power (HT), dBA	65
Sound Power with Sound Shell (HT), dBA	59
Sound Conditions (HT, Temperatures:	7 / 54 / 18 °C at 50 Hz
Evap./Cond./Suction at freq./speed)	
PED Category	1
Max. Internal Free Volume, l	2.90
High Side PS gauge, bar	29.5
Low Side PS gauge, bar	20
Low Side TS Max., °C	50
Refrigerant's GWP	1430
Refrigerant's classification	A1

### **COMPRESSOR ELECTRICAL DATA (220-240 V / 1~ / 50 Hz)**

Maximum Operating Current, A	14.8
Locked Rotor Current, A	61
Winding Resistance, ohm	1.2/2.23 (R/S)
Default Enclosure Class	IP 21 (IEC 34)

### **ACCESSORIES INCLUDED**

Discharge Temperature Protection	Internal Thermodisk
Mounting Grommets	Standard

### **ACCESSORIES OPTIONAL**

Crankcase Heater	70 W External
Single Phase Equipment	Run Capacitor

**MOTOR OPTIONS**

<b>Motor Code</b>	<b>Power Supply</b>	<b>Nominal Voltage, V</b>	<b>Start Connection</b>	<b>DOL Connection</b>	<b>Amps Factor</b>
PFJ	220-240 V / 1~ / 50 Hz	230		PSC	1.00
PFJ	265 V / 1~ / 60 Hz	265		PSC	0.75