



Minimum Evaporating Temp. With:	
— 20 K Suction Superheat	— 20 K Suction Superheat Liquid injection
— 20 °C Suction Gas Return Liquid injection	— Maximum Evaporating Temperature
— Maximum Pressure Limit	

Suction Return Temperature 18.3°C

Liquid Subcooling 0.0K

Evaporating Temperature, °C

Ambient °C	Cooling Capacity, kW										
	-40.0	-35.0	-30.0	-25.0	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0
27.0	3.70	4.75	5.94	7.31	8.87	10.60	12.55	14.70	17.00	19.55	20.60
32.0	3.57	4.56	5.69	6.97	8.43	10.05	11.85	13.85	16.00		
38.0											
43.0											
46.0											
49.0											

Ambient °C	Total Power Input, kW										
	-40.0	-35.0	-30.0	-25.0	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0
27.0	3.00	3.33	3.65	3.96	4.27	4.57	4.87	5.17	5.47	5.77	5.89
32.0	3.34	3.70	4.04	4.38	4.70	5.02	5.33	5.64	5.94		
38.0											
43.0											
46.0											
49.0											

Ambient °C	Current at 400 V, A										
	-40.0	-35.0	-30.0	-25.0	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0
27.0	4.31	4.99	5.63	6.23	6.79	7.32	7.82	8.29	8.73	9.13	9.28
32.0	5.03	5.73	6.38	6.98	7.54	8.06	8.54	8.98	9.38		
38.0											
43.0											
46.0											
49.0											

Ambient °C	Mass Flow, g/s										
	-40.0	-35.0	-30.0	-25.0	-20.0	-15.0	-10.0	-5.0	0.0	5.0	7.0
27.0	15.75	20.70	26.50	33.60	42.00	52.00	63.90	77.80	94.00	112.50	121.00
32.0	15.40	20.20	26.00	32.80	41.00	50.80	62.40	76.10	92.00		
38.0											
43.0											
46.0											
49.0											

CONDENSING UNIT MECHANICAL AND PHYSICAL DATA

Condenser/Fan Type	ZXL_2F/60 W
Number of Fans	2
Total Fan Power Input, W	246
Depth/Width, mm	1035/447
Height, mm	1244
Base mounting (hole dia), mm	580 x 388 (12)
Net Weight, kg	116
Receiver Capacity, l	5.9
Liquid Line, inch	1/2
Air Flow, m ³ /s	1.64
High Side PS gauge, bar	28.8
Low Side PS gauge, bar	21
Suction Type	Cu Tube
Suction Diameter, inch	7/8
Sound Pressure @ 10m (LT), dBA	41
Sound Pressure @ 10m (MT), dBA	41
Sound Conditions (LT, Temperatures: Evap./Cond./Suction at freq./speed)	-35.0/40.0/20.0 °C at 50 Hz
Sound Conditions (MT, Temperatures: Evap./Cond./Suction at freq./speed)	-10.0/45.0/20.0 °C at 50 Hz

CONDENSING UNIT ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)

Compressor Maximum Operating Current, A	13.7
Compressor Locked Rotor Current, A	74

ACCESSORIES INCLUDED

Crankcase Heater	70 W External
Oil separator	ALCO OSH-404
Liquid sight glass	ALCO MIA 012
Compressor contactor	12 A
Control circuit fuse	S7-904-5355-0
HP Switch	ALCO PS3 WDS (Automatic reset)
Electronic controller	Emerson XCM25D
Filter Drier	ALCO ADK Plus
Vapour Injection	Expansion Valve
Circuit breaker, over current relay	20 A
Suction Accumulator	ALCO A12-507

50 Hz

ZXLE-060E-TFD

R449A Dew Point

ACCESSORIES OPTIONAL

LP Adjustable Pressure Switch

Alco PS1-A3A

MOTOR OPTIONS

<i>Motor Code</i>	<i>Power Supply</i>	<i>Nominal Voltage, V</i>	<i>Start Connection</i>	<i>DOL Connection</i>	<i>Amps Factor</i>
TFD	380-420 V / 3~ / 50 Hz	400		Y	1.00