




Minimum Evaporating Temp. With:

- 10 K Suction Superheat — 20 °C Suction Gas Return
- Maximum Evaporating Temperature

Compatibility with A2L refrigerants for manufacturing date after 10 2021 only

50 Hz	4MF-13	R454C Dew Point
Suction Return Temperature 18.3°C		Liquid Subcooling 0.0K

Evaporating Temperature, °C

Cond °C	Cooling Capacity, kW							
	-35.0	-30.0	-25.0	-20.0	-15.0	-10.0	-5.0	0.0
10.0	13.50	17.40	22.30	28.20	35.20			
15.0	12.60	16.35	21.00	26.60	33.30	41.10		
20.0	11.75	15.30	19.70	25.00	31.30	38.70	47.10	56.80
25.0	10.90	14.30	18.45	23.50	29.40	36.30	44.30	53.40
30.0	10.05	13.25	17.20	21.90	27.50	34.00	41.50	50.00
35.0		12.25	15.95	20.40	25.60	31.70	38.70	46.70
40.0		11.25	14.75	18.85	23.70	29.30	35.80	43.30
45.0			13.50	17.30	21.80	27.00	33.10	40.00
50.0			12.30	15.80	19.95	24.70	30.30	36.60
55.0				14.30	18.05	22.40	27.50	33.30
60.0					16.20	20.10	24.70	30.00
65.0					14.35	17.85	22.00	26.70
70.0						15.60	19.20	

Cond °C	Power, kW							
	-35.0	-30.0	-25.0	-20.0	-15.0	-10.0	-5.0	0.0
10.0	4.49	4.98	5.40	5.71	5.90			
15.0	4.80	5.36	5.86	6.27	6.57	6.72		
20.0	5.07	5.71	6.29	6.80	7.21	7.49	7.60	7.54
25.0	5.30	6.01	6.69	7.30	7.83	8.24	8.50	8.59
30.0	5.48	6.27	7.05	7.77	8.42	8.96	9.37	9.63
35.0		6.49	7.36	8.20	8.97	9.66	10.20	10.65
40.0		6.66	7.63	8.59	9.49	10.30	11.05	11.65
45.0			7.86	8.94	9.98	10.95	11.85	12.60
50.0			8.04	9.25	10.45	11.55	12.60	13.55
55.0				9.51	10.85	12.10	13.35	14.50
60.0					11.20	12.65	14.05	15.35
65.0					11.50	13.15	14.70	16.25
70.0						13.55	15.35	

Compatibility with A2L refrigerants for manufacturing date after 10 2021 only

50 Hz

4MF-13

R454C Dew Point

Cond °C	Current at 400 V, A							
	-35.0	-30.0	-25.0	-20.0	-15.0	-10.0	-5.0	0.0
10.0	9.63	10.24	10.77	11.17	11.40			
15.0	10.01	10.70	11.34	11.87	12.26	12.45		
20.0	10.34	11.13	11.88	12.56	13.11	13.49	13.65	13.55
25.0	10.63	11.52	12.40	13.22	13.95	14.52	14.90	15.05
30.0	10.85	11.86	12.88	13.86	14.77	15.55	16.16	16.56
35.0		12.15	13.31	14.47	15.56	16.56	17.41	18.06
40.0		12.38	13.70	15.03	16.33	17.55	18.64	19.57
45.0			14.02	15.54	17.05	18.50	19.85	21.06
50.0			14.27	15.99	17.72	19.42	21.03	22.53
55.0				16.37	18.33	20.28	22.18	23.97
60.0					18.88	21.10	23.27	25.38
65.0					19.36	21.85	24.32	26.74
70.0						22.53	25.30	

Cond °C	Suction Mass Flow, g/s							
	-35.0	-30.0	-25.0	-20.0	-15.0	-10.0	-5.0	0.0
10.0	64.10	83.00	106.50	135.50	170.00			
15.0	62.10	80.80	104.00	132.50	166.50	206.00		
20.0	60.10	78.50	101.50	129.50	162.50	202.00	248.00	301.00
25.0	57.90	76.20	98.80	126.00	159.00	197.50	242.00	295.00
30.0	55.80	73.90	96.10	123.00	155.00	193.00	237.00	288.00
35.0		71.40	93.30	119.50	151.00	188.00	231.00	282.00
40.0		68.80	90.30	116.00	147.00	183.00	225.00	275.00
45.0			87.30	112.50	142.50	178.00	219.00	268.00
50.0			84.10	109.00	138.00	172.50	213.00	260.00
55.0				105.00	133.50	167.00	207.00	253.00
60.0					128.50	161.00	200.00	245.00
65.0					123.50	155.50	193.00	237.00
70.0						149.50	186.00	

Compatibility with A2L refrigerants for manufacturing date after 10 2021 only

COMPRESSOR MECHANICAL AND PHYSICAL DATA

Number of cylinders	4
Displacement @ 50 Hz, m ³ /h	61.7
Bore/Stroke, mm	63.5/56.0
Length/Width, mm	638/501
Height, mm	452
Net Weight, kg	177
Suction, inch	1 5/8
Discharge, inch	1 1/8
Oil Quantity, l	3.3
Oil type (original charge)	POE RL32-3MAF
Oil type (approved oils)	POE RL32-3MAF
Base mounting (hole dia), mm	381 x 305 (18)
Sound Pressure @ 1m (LT), dBA	70
Sound Power (LT), dBA	81
Sound Conditions (LT, Temperatures: Evap./Cond./Suction at freq./speed)	-35 / 40 / 20 °C at 50 Hz
Sound Pressure @ 1m (MT), dBA	68
Sound Power (MT), dBA	79
Sound Conditions (MT, Temperatures: Evap./Cond./Suction at freq./speed)	-10 / 45 / 20 °C at 50 Hz
High Side PS gauge, bar	32.5
Low Side PS gauge, bar	22.5
Refrigerant's GWP	148
Refrigerant's classification	A2L

COMPRESSOR ELECTRICAL DATA (380-420 V / 3~ / 50 Hz)

Maximum Operating Current, A	30.8
Locked Rotor Current, A	105
Default Enclosure Class	IP 54 (IEC 34)

Compatibility with A2L refrigerants for manufacturing date after 10 2021 only

ACCESSORIES INCLUDED

Mounting Parts	Spring
CoreSense Protection (-P)	Motor protection
Oil Pressure Switch (-P)	OPS2 Sensor
Copeland Compressor Electronic (-N)	Oil pressure, motor and discharge line temperature protection; advanced diagnostics features and power measurement

ACCESSORIES OPTIONAL

Additional Cooling	70 W Vertical Air Flow Fan
Capacity Control	Capacity Steps 50%
Crankcase Heater	100 W Internal
Oil Pressure Switch	OPS2 Electronic Switch
Adapter Kit	For Parallel Operation
Check Valve	For unloaded start operation
Sound Attenuation	Sound Shell
Mounting Parts	Rubber
Copeland Compressor Electronic module	Modbus extension module

MOTOR OPTIONS

<i>Motor Code</i>	<i>Power Supply</i>	<i>Nominal Voltage, V</i>	<i>Start Connection</i>	<i>DOL Connection</i>	<i>Amps Factor</i>
AWM	380-420 V / 3~ / 50 Hz	400	YY/Y	Y	1.00
EWL	220-240 V / 3~ / 50 Hz	230	Y/DELTA	DELTA	1.73
EWL	380-420 V / 3~ / 50 Hz	400		Y	1.00
EWM	380-420 V / 3~ / 50 Hz	400	Y/DELTA	DELTA	1.00
AWR	220-240 V / 3~ / 50 Hz	230	YY/Y	Y	1.73
AWY	500-550 V / 3~ / 50 Hz	525	YY/Y	Y	0.76
EWK	220-240 V / 3~ / 60 Hz	230	Y/DELTA	DELTA	2.10
EWK	380-420 V / 3~ / 60 Hz	380		Y	1.20
EWD	440-480 V / 3~ / 60 Hz	460	Y/DELTA	DELTA	1.00
AWC	208-230 V / 3~ / 60 Hz	230	YY/Y	Y	2.19
AWX	380 V / 3~ / 60 Hz	380	YY/Y	Y	1.20
AWD	440-480 V / 3~ / 60 Hz	460	YY/Y	Y	1.00

Compatibility with A2L refrigerants for manufacturing date after 10 2021 only